

# PROSTRENGTH RAPID SET MORTAR

**HARDENS  
IN 10 MINS**  
further construction  
can take place  
after 1 hour



- ✓ **Easy to use** – for smaller jobs mix only enough material required directly in the bucket
- ✓ **Excellent bond to concrete and masonry**
- ✓ **1 bucket is enough to bed 1 standard toilet pan** - covers approximately 1m<sup>2</sup> at 2mm thick

Build with Confidence

[cementaustralia.com.au](http://cementaustralia.com.au)



LOCALLY MADE  
AUSTRALIAN  
PRODUCT





Suitable for around the home and building site, patching around electric and plumbing fittings, re-pointing on block, brick and rendered surfaces.



- ✔ A quality blend of cement, graded sand & specialty additives
- ✔ Excellent workability
- ✔ Just add water into the bucket and mix (no mess, no fuss)
- ✔ For fast repairs around the home and building sites
- ✔ Good for small jobs – convenient & easy to use
- ✔ Suitable for both internal and external use

**Examples of Use:**



Before: Drain Base Repair



After: Drain Base Repair



Before: Driveway Repair



After: Driveway Repair

The recommended shelf life of PROStrength Rapid Set Mortar is approximately 12 months from the date of manufacture when stored properly in a dry location, protected from moisture, out of direct sunlight, and in an undamaged package.



TOILET PAN BEDDING



PLUGGING & GROUTING



FIXING BRICKWORK

**SUGGESTIONS FOR USE**

Add water gradually (approx 1.4 litres per 8kg bucket / 175ml per 1kg of dry product) and blend thoroughly to achieve a workable mix. *Note:* Additional water may prolong setting and weaken the overall strength of the mortar.

**IMPORTANT** Ensure you are able to quickly transfer the blended mortar to the area you are applying it to, in order to avoid it setting in the mixing vessel. Product is expected to stiffen in 10 minutes, recommended to ensure product is placed within 5 minutes.

Ambient temperatures may prolong or shorten set times; product will work best in working conditions between 10°C and 32°C.

Apply the PROStrength Rapid Set Mortar as required to complete the task at hand.

**Tips**

- Clean all tools and equipment with water without delay after use.
- Hot temperatures will impact set times, avoid working in direct sunlight.
- For non-structural applications.

Item Code 17732

Cement Australia  
PROStrength  
Rapid Set Mortar 8kg

