



HYDRATED LIME

Blends with sand & cement for mortar & render
Enhances mortar bond strength & workability
Conforms to AS 1672.1 Limes for Building



CEMENT AUSTRALIA®

plus water treatment,
sanitising & pH adjustments


HYDRATED LIME

- ✓ Blends with sand and cement for mortar
- ✓ Enhances mortar bond strength and workability
- ✓ Also suitable for landscaping and agricultural applications

Build with Confidence

cementaustralia.com.au or call 1300 CEMENT (1300 236 368)

CEMENT AUSTRALIA®



MORTAR



GARDENING & AGRICULTURE



RENDER

Cement Australia Hydrated Lime is a highly alkaline product used in many industrial, agricultural and construction applications. Hydrated Lime can be used in cement/sand mortars and renders to improve workability, plasticity and durability




- ✓ Improves the workability of mortar and render
- ✓ Enhances bond strength when used in cement/sand mortar and render
- ✓ Assists in water retention in mortar
- ✓ Good for small jobs or where access is limited
- ✓ 20kg bagged product is convenient and easy to use

STANDARD MIX RATIOS (BY VOLUME)

Application	Cement	Sand	Hydrated Lime
Mortar (enhanced workability)	1	6	1

Ratios reflect Australian Standard AS3700 Type M3 Mortar

HOW TO USE

-  **STEP 1** Combine lime, cement and sand in correct proportion in a non-porous vessel. Large jobs require a mortar mixer.
-  **STEP 2** Add drinkable water gradually and mix thoroughly. Use enough water to make a workable mix.
-  **STEP 3** Apply the mix with a trowel.

HANDLING AND LIMITATIONS

Do not allow the mixed mortar to stand for an extended period of time, as re-tempering the mix with additional water will weaken the mortar.

Hydrated Lime is an extremely alkaline substance and care should be taken when handling to avoid contact with skin, eyes and lips.

To view all product limitations, storage & handling tips please visit cementaustralia.com.au

Item Code 14496

Cement Australia
Hydrated Lime 20kg



PRODUCT DISCLAIMER

Recommendations regarding the use of this product are to be taken as a guide only. If in doubt contact Cement Australia Pty Limited ("Cement Australia") or seek professional advice. To the extent permitted by law, Cement Australia excludes all implied warranties, conditions and guarantees imposed by legislation. Cement Australia excludes all liability for loss, damage or injury arising from use of the product (i) otherwise than in accordance with the recommendations or (ii) for purposes other than those for which it is ordinarily acquired. For all other loss, damage or injury arising from the use of this product, to the extent permitted by law Cement Australia's liability is limited, at its discretion, to refunding the cost of the product or resupplying the product or equivalent product.

Safety Data Sheet available at cementaustralia.com.au

